

## **PRODUCT DATA SHEET**

### **Cable Description**

<b>Cable Size</b>	:	150 mm <sup>2</sup>
<b>Standard Specification Applied To Cable</b>	:	IEC 60227 - IEC 60228
<b>Rated Voltage</b>	:	450 / 750 Volt
<b>Cable Description</b>	:	Flexible Copper Conductor Insulated With Polyvinyl Chloride (CU / PVC)

### **Conductor**

<b>Standard Specification Applied To Conductor</b>	:	IEC 60228
<b>NO. Of Cores per Cable</b>	:	1
<b>Nominal Cross- Sectional Area Per core</b>	:	150.0 mm <sup>2</sup>
<b>Nominal Number Of Strands Per core</b>	:	2100
<b>Diameter Of Each Strand</b>	:	0.30 mm
<b>Material Of Core</b>	:	Copper
<b>Type</b>	:	Class-5
<b>Cross- Sectional Area Of Each Strand</b>	:	0.07065 mm <sup>2</sup>
<b>Overall Diameter Of Conductor</b>	:	19.00 mm
<b>D.C. Resistance Of Conductor At 20°C Per Km (max.)</b>	:	0.129 Ω/km

### **Insulation**

<b>Material Of Insulation</b>	:	Polyvinyl Chloride
<b>Colour Per Core</b>	:	.....
<b>Nominal Thickness Of Insulation Per Core</b>	:	1.80 mm
<b>Min. Insulation Resistance Per Core Per Km Length Of Cable At 70°C</b>	:	0.0029 M ohm.Km
<b>Test Voltage Between Cores And Earth ( AC KV . Time min )</b>	:	2500V for 5 min
<b>Heat Resistance Test ( Temperature °C . Time min )</b>	:	150 °C for 1 hour

### **Over Sheath**

<b>Material Of Outer Jacket</b>	:	.....
<b>Thickness Of Outer Jacket</b>	:	.....
<b>Colour Of Outer Jacket</b>	:	.....

### **Cable Dimension ( Nominal ) :**

<b>Nominal External Cable Diameter</b>	:	18.6 : 22.5 mm
--	---	----------------