

PRODUCT DATA SHEET

Cable Description

Cable Size	:	25 mm ²
Standard Specification Applied To Cable	:	IEC 60227 - IEC 60228
Rated Voltage	:	450 / 750 Volt
Cable Description	:	Flexible Copper Conductor Insulated With Polyvinyl Chloride (CU / PVC)

Conductor

Standard Specification Applied To Conductor	:	IEC 60228
NO. Of Cores per Cable	:	1
Nominal Cross- Sectional Area Per core	:	25.0 mm ²
Nominal Number Of Strands Per core	:	350
Diameter Of Each Strand	:	0.30 mm
Material Of Core	:	Copper
Type	:	Class-5
Cross- Sectional Area Of Each Strand	:	0.07065 mm ²
Overall Diameter Of Conductor	:	7.50 mm
D.C. Resistance Of Conductor At 20°c Per Km (max.)	:	0.78 Ω/km

Insulation

Material Of Insulation	:	Polyvinyl Chloride
Colour Per Core	:
Nominal Thickness Of Insulation Per Core	:	1.20 mm
Min. Insulation Resistance Per Core Per Km Length Of Cable At 70°c	:	0.0044 M ohm.Km
Test Voltage Between Cores And Earth (AC KV . Time min)	:	2500V for 5 min
Heat Resistance Test (Temperature °c . Time min)	:	150 °c for 1 hour

Over Sheath

Material Of Outer Jacket	:
Thickness Of Outer Jacket	:
Colour Of Outer Jacket	:

Cable Dimension (Nominal) :

Nominal External Cable Diameter	:	8.4 : 10.2 mm
--	---	---------------