

PRODUCT DATA SHEET

Cable Description

Cable Size	:	3X240 mm ² + 120 mm ²
Standard Specification Applied To Cable	:	IEC 60502 - IEC 60228
Rated Voltage	:	600 / 1000 Volt
Cable Description	:	Stranded Copper Conductor Insulated With Polyvinyl Chloride And Sheathed With Polyvinyl Chloride(CU / PVC / PVC)

Conductor

Standard Specification Applied To Conductor	:	IEC 60228	
NO. Of Cores per Cable	:	3	1
Nominal Cross- Sectional Area Per core	:	240 mm ²	
Nominal Number Of Strands Per core	:	61	37
Diameter Of Each Strand	:	2.25 mm	2.02mm
Material Of Core	:	Copper	Copper
Type	:	Class-2	Class-2
Cross- Sectional Area Of Each Strand	:	3.974 mm ²	
Overall Diameter Of Conductor	:	20.25 mm	14.15mm
D.C. Resistance Of Conductor At 20°C Per Km (max.)	:	0.0754 Ω/km	0.153 Ω/km

Insulation

Material Of Insulation	:	Polyvinyl Chloride	
Colour Per Core	:	Red – Yellow – Blue	Black
Nominal Thickness Of Insulation Per Core	:	2.20 mm	1.60mm
Min. Insulation Resistance Per Core Per Km Length Of Cable At 70°C	:	0.0032 M ohm.Km	
Test Voltage Between Cores And Earth (AC KV . Time min)	:	3000V for 5 min	
Heat Resistance Test (Temperature °C . Time min)	:	150 °C for 1 hour	

Over Sheath

Material Of Outer Jacket	:	Polyvinyl Chloride
Thickness Of Outer Jacket	:	2.90 mm
Colour Of Outer Jacket	:	Gray Or Black

Cable Dimension (Nominal) :

Approx. External Cable Diameter	:	61.00 mm
--	---	----------