

PRODUCT DATA SHEET

Cable Description

Cable Size	:	3X35 mm ² +16 mm ²
Standard Specification Applied To Cable	:	IEC 60502 - IEC 60228
Rated Voltage	:	600 / 1000 Volt
Cable Description	:	Stranded Copper Conductor Insulated With Polyvinyl Chloride And Sheathed With Polyvinyl Chloride(CU / PVC / PVC)

Conductor

Standard Specification Applied To Conductor	:	IEC 60228	
NO. Of Cores per Cable	:	3	1
Nominal Cross- Sectional Area Per core	:	35 mm ²	
Nominal Number Of Strands Per core	:	19	7
Diameter Of Each Strand	:	1.50 mm	1.70mm
Material Of Core	:	Copper	Copper
Type	:	Class-2	Class-2
Cross- Sectional Area Of Each Strand	:	1.766 mm ²	
Overall Diameter Of Conductor	:	7.5 mm	5.1mm
D.C. Resistance Of Conductor At 20°c Per Km (max.)	:	0.524 Ω/km	1.15 Ω/km

Insulation

Material Of Insulation	:	Polyvinyl Chloride	
Colour Per Core	:	Red – Yellow – Blue	Black
Nominal Thickness Of Insulation Per Core	:	1.20 mm	1.00mm
Min. Insulation Resistance Per Core Per Km Length Of Cable At 70°c	:	0.0043 M ohm.Km	
Test Voltage Between Cores And Earth (AC KV . Time min)	:	3000V for 5 min	
Heat Resistance Test (Temperature °c . Time min)	:	150 °c for 1 hour	

Over Sheath

Material Of Outer Jacket	:	Polyvinyl Chloride
Thickness Of Outer Jacket	:	1.80 mm
Colour Of Outer Jacket	:	Gray Or Black

Cable Dimension (Nominal) :

Approx. External Cable Diameter	:	25.90 mm
--	---	----------