

PRODUCT DATA SHEET

Cable Description

Cable Size	:	3X50 mm ² + 25 mm ²
Standard Specification Applied To Cable	:	IEC 60502 - IEC 60228
Rated Voltage	:	600 / 1000 Volt
Cable Description	:	Stranded Copper Conductor Insulated With Polyvinyl Chloride And Sheathed With Polyvinyl Chloride(CU / PVC / PVC)

Conductor

Standard Specification Applied To Conductor	:	IEC 60228	
NO. Of Cores per Cable	:	3	1
Nominal Cross- Sectional Area Per core	:	50 mm ²	
Nominal Number Of Strands Per core	:	19	19
Diameter Of Each Strand	:	1.80 mm	1.30mm
Material Of Core	:	Copper	Copper
Type	:	Class-2	Class-2
Cross- Sectional Area Of Each Strand	:	2.543mm ²	
Overall Diameter Of Conductor	:	9.00 mm	6.5mm
D.C. Resistance Of Conductor At 20° Per Km (max.)	:	0.387 Ω/km	0.727 Ω/km

Insulation

Material Of Insulation	:	Polyvinyl Chloride	
Colour Per Core	:	Red – Yellow – Blue	Black
Nominal Thickness Of Insulation Per Core	:	1.40 mm	1.2mm
Min. Insulation Resistance Per Core Per Km Length Of Cable At 70°	:	0.0043 M ohm.Km	
Test Voltage Between Cores And Earth (AC KV . Time min)	:	3000V for 5 min	
Heat Resistance Test (Temperature ° . Time min)	:	150 ° for 1 hour	

Over Sheath

Material Of Outer Jacket	:	Polyvinyl Chloride
Thickness Of Outer Jacket	:	1.90 mm
Colour Of Outer Jacket	:	Gray Or Black

Cable Dimension (Nominal) :

Approx. External Cable Diameter	:	30.60 mm
--	---	----------