

PRODUCT DATA SHEET

Cable Description

| | | |
|--|---|--|
| <i>Cable Size</i> | : | 4X1.5 mm ² |
| <i>Standard Specification Applied To Cable</i> | : | IEC 60502 - IEC 60228 |
| <i>Rated Voltage</i> | : | 600 / 1000 Volt |
| <i>Cable Description</i> | : | Stranded Copper Conductor Insulated With Polyvinyl Chloride And Sheathed With Polyvinyl Chloride(CU / PVC / PVC) |

Conductor

| | | |
|---|---|------------------------|
| <i>Standard Specification Applied To Conductor</i> | : | IEC 60228 |
| <i>NO. Of Cores per Cable</i> | : | 4 |
| <i>Nominal Cross- Sectional Area Per core</i> | : | 1.5 mm ² |
| <i>Nominal Number Of Strands Per core</i> | : | 7 |
| <i>Diameter Of Each Strand</i> | : | 0.53 mm |
| <i>Material Of Core</i> | : | Copper |
| <i>Type</i> | : | Class-2 |
| <i>Cross- Sectional Area Of Each Strand</i> | : | 0.2205 mm ² |
| <i>Overall Diameter Of Conductor</i> | : | 1.60 mm |
| <i>D.C. Resistance Of Conductor At 20°c Per Km (max.)</i> | : | 12.10 Ω/km |

Insulation

| | | |
|---|---|-----------------------------|
| <i>Material Of Insulation</i> | : | Polyvinyl Chloride |
| <i>Colour Per Core</i> | : | Red – Yellow – Blue - Black |
| <i>Nominal Thickness Of Insulation Per Core</i> | : | 0.80 mm |
| <i>Min. Insulation Resistance Per Core Per Km Length Of Cable At 70°c</i> | : | 0.010 M ohm.Km |
| <i>Test Voltage Between Cores And Earth (AC KV . Time min)</i> | : | 3000V for 5 min |
| <i>Heat Resistance Test (Temperature °c . Time min)</i> | : | 150 °c for 1 hour |

Over Sheath

| | | |
|----------------------------------|---|--------------------|
| <i>Material Of Outer Jacket</i> | : | Polyvinyl Chloride |
| <i>Thickness Of Outer Jacket</i> | : | 1.80 mm |
| <i>Colour Of Outer Jacket</i> | : | Gray Or Black |

Cable Dimension (Nominal) :

| | | |
|--|---|----------|
| <i>Approx. External Cable Diameter</i> | : | 11.30 mm |
|--|---|----------|