

PRODUCT DATA SHEET

Cable Description

| | | |
|--|---|--|
| Cable Size | : | 4X185 mm ² |
| Standard Specification Applied To Cable | : | IEC 60502 - IEC 60228 |
| Rated Voltage | : | 600 / 1000 Volt |
| Cable Description | : | Flexible Copper Conductor Insulated With Polyvinyl Chloride And Sheathed With Polyvinyl Chloride(CU / PVC / PVC) |

Conductor

| | | |
|---|---|-------------------------|
| Standard Specification Applied To Conductor | : | IEC 60228 |
| NO. Of Cores per Cable | : | 4 |
| Nominal Cross- Sectional Area Per core | : | 185 mm ² |
| Nominal Number Of Strands Per core | : | 2590 |
| Diameter Of Each Strand | : | 0.30 mm |
| Material Of Core | : | Copper |
| Type | : | Class-5 |
| Cross- Sectional Area Of Each Strand | : | 0.07065 mm ² |
| Overall Diameter Of Conductor | : | 21.0 mm |
| D.C. Resistance Of Conductor At 20°c Per Km (max.) | : | 0.106 Ω/km |

Insulation

| | | |
|---|---|-----------------------------|
| Material Of Insulation | : | Polyvinyl Chloride |
| Colour Per Core | : | Red – Yellow – Blue – Black |
| Nominal Thickness Of Insulation Per Core | : | 2.00 mm |
| Min. Insulation Resistance Per Core Per Km Length Of Cable At 70°c | : | 0.0032 M ohm.Km |
| Test Voltage Between Cores And Earth (AC KV . Time min) | : | 3000V for 5 min |
| Heat Resistance Test (Temperature °c . Time min) | : | 150 °c for 1 hour |

Over Sheath

| | | |
|----------------------------------|---|--------------------|
| Material Of Outer Jacket | : | Polyvinyl Chloride |
| Thickness Of Outer Jacket | : | 3.00 mm |
| Colour Of Outer Jacket | : | Gray Or Black |

Cable Dimension (Nominal) :

| | | |
|--|---|----------|
| Approx. External Cable Diameter | : | 66.00 mm |
|--|---|----------|